





1200 x 1000 x 165

Recycled HDPE or PP

24


7000


2500

1200

-20 to+40

## 1200 X 1000 | 3 RUNNERS | CLOSED DECK





TECHNICAL DATA

Material

Measures (mm)

Weight (kg +/- 3%)

Static load\* (kg)

Dynamic load\*\* (kg)

Load in rack\*\*\* (kg)

## **OPTIONS**

No lip / Anti-slip strips / Special color / RFID / Forklift supporting areas

PACKAGING	(indicative values)
Packaging unit (pcs)	15
Bulk size (mm)	1200 x 1000 x 2495
Truck (pcs)	390


Truck (pcs)	390
PERSONALIZED MARKING (	consult conditions)

Silkscreen printing / Heat stamped / Mold engraving

## CHARACTERISTICS Standard color Anthracite Lip (mm) 5,5



Temperature range (°C)









\*Static load: Uniformly distributed load which the pallet can support when placed on a flat, horizontal rigid surface, at a temperature of approximately 20°C.

\*\*Dynamic load: Uniformly distributed load which the pallet can support when transported or manoeuvred on a conventional forklift or pallet truck, at a temperature of approximately 20°C.

\*\*Load in rack: Uniformly distributed load which the pallet can support when resting on the skids on its short side on a standard rack, at a temperature of approximately 20°C.

The indicated values are approximate and based on experience and practical cases.

Any deterioration or different loading, temperature or storage method conditions, can cause this data to vary.

We reserve the right to modify any information provided herein without prior notice.

We recommend testing the pallet before use.